



LAWRENCE
LIVERMORE
NATIONAL
LABORATORY

Radiation transport through cylindrical foams with heated walls

K. L. Baker, S. A. Maclaren, J. B. Kallman, W. W.
Hsing

October 29, 2012

54th Annual Meeting of the APS Division of Plasma Physics
Providence, RI, United States
October 29, 2012 through November 2, 2012

Disclaimer

This document was prepared as an account of work sponsored by an agency of the United States government. Neither the United States government nor Lawrence Livermore National Security, LLC, nor any of their employees makes any warranty, expressed or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States government or Lawrence Livermore National Security, LLC. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States government or Lawrence Livermore National Security, LLC, and shall not be used for advertising or product endorsement purposes.

Radiation Transport through cylindrical foams with heated walls

Kevin Baker, Steve MacLaren, Joshua Kallman, Ken Heinz, Warren Hsing

Lawrence Livermore National Laboratory, 7000 East Ave., Livermore, CA, 94551

Radiation transport through low density SiO_2 foams has been experimentally studied on the Omega laser. In particular these experiments examined the effects on radiation transport when the boundaries of the SiO_2 foam are heated such that energy loss to the boundaries is minimized. The initial density of the SiO_2 foams was determined by taking an x-ray radiograph of the foams using a monochromatic Henke source at multiple x-ray energies. The radiation drive used to both study the transport in the SiO_2 foam as well as to heat the higher density CRF wall was generated in a laser-heated gold hohlraum using ~ 7.5 kJ of the laser energy. The time-dependent spatial profile of the heat wave breaking out of the SiO_2 foam was detected with an x-ray streak camera coupled with a soft x-ray transmission grating. The Omega DANTE diagnostic measured the radiation drive in the hohlraum and the Omega VISAR diagnostic monitored the spatial temperature gradient in the foam section of the hohlraum. This work was performed under the auspices of the U.S. Department of Energy by Lawrence Livermore National Laboratory under Contract DE-AC52-07NA27344.